

EQUIPMENT



Height-adjustable head joint made of powder-coated steel, with trapezoid Head pillow without cavity.



Height adjustment at the push of a foot.



Central braking system effective on all four wheels.



25 x 10 mm standard rail for the attachment of accessories.

SPECIFICATIONS

Chassis

- Frame profile 60 x 60 mm
- Outside length 1,140 mm
- Outside width 650 mm
- Caster, electrically conductive ø 150 mm

Lifting Column

- Foot hydraulic 560/910 mm
- Height adjustment min./max. 2,000 N
- Max. lifting force 1,500 N
- Footrest section 800 N
- Backrest section 300 N
- Headrest section 100 bar
- Operating pressure ca. 0.7 liter
- Hydraulic oil, DTE 10 EXCEL 32 0° to +40° C
- Ambient temperature range

Upper Frame

- 3-part support frame (head, back, foot)
- Length 2,090 mm
- Width 650 mm
- Foot adjustment 0°/+15°
- Back adjustment 0°/+55°
- Head adjustment -20°/+30°
- Trendelenburg/Reverse Trendelenburg +18°/-13°
- Height adjustment range 360 mm
- Standard stainless steel side rails, both sides 25 x 10 mm
- Upholstery, electrically conductive 40 mm

Max. Load

150 kg

Weight

115 kg

Subject to technical modifications.

Height-adjustable Head element.



Central brake system.

